

HDS Nomex 5 1/4" Midwoofer



Type Number: 832873

Features:

The High Definition Sound (HDS) NOMEX Series offers high-quality solutions for both multi-way speaker systems and vented box applications. Featuring "shorting rings" for low distortion and coils offering perfect linear compatibility with NOMEX cones, these audio transducers are characterized by their very open, very rich sound character.

Driver Highlights: Nomex diaphragm, 26 mm coil, AL

[Go to Architecture Notes](#)



Specs:

Electrical Data

Nominal impedance	Zn	8	ohm
Minimum impedance	Zmin	6.5	ohm
Maximum impedance	Zo	37.3	ohm
DC resistance	Re	6	ohm
Voice coil inductance	Le	0.8	mH

T-S Parameters

Resonance Frequency	fs	58.6	Hz
Mechanical Q factor	Qms	2.39	
Electrical Q factor	Qes	0.46	
Total Q factor	Qts	0.38	
Ratio fs/Qts	F	152	
Force factor	Bl	6.6	Tm
Mechanical resistance	Rms	1.4	Kg/s
Moving mass	Mms	9.1	g
Suspension compliance	Cms	0.81	mm/N
Effective cone diameter	D	10.6	cm
Effective piston area	Sd	88	cm ²
Equivalent volume	Vas	8.7	ltrs
Sensitivity		88.3	dB
Ratio BL/√(Re)		2.7	


Power handling

100h RMS noise test (IEC)	--	W
Long-term Max System Power (IEC)	--	W
Max linear SPL (rms) @ power	--	dB/W
Short Term Max power	--	W

Voice Coil and Magnet Parameters

Voice coil diameter	26	mm
Voice coil height	13	mm
Voice coil layers	2	
Height of the gap	6	mm
Linear excursion +/-	3.5	mm
Max mech. excursion +/-	--	mm
Flux density of gap	--	mWb
Total useful flux	0.7	mWb
Diameter of magnet	90	mm
Height of magnet	15	mm
Weight of magnet	0.4	Kg

Frequency:



Mechanical Dimensions:

