

silky

Product Description

Construction

Product Description	Methods	Product Data
Structure	ISO 2424	Tufted cut pile
Gauge	ISO 2424	5/32
Pile material	DIR 96/73, 96/74	100% Polyamide
Coloration	-	Continue
Backing	eTL	LL - Luxury latex
Dimensions	ISO 3018	400 cm
Total thickness	ISO 1765	17,4 mm.
Surface pile thickness	ISO 1766	8,0 mm.
Tufts	ISO 1763	51.700 pr. m2
Total carpet weight	ISO 8543	4.000 g/m2
Pile yarn weight	eTL	1.500 g/m2
Surface pile density	ISO 8543	0,152 g/cm3
Antisoiling protection	eTL	Yes

Performance ratings

Performance areas	EN 1307	23 Domestic - Heavy
Static control	eTL	Permanently antistatic
Colour fastness to light	ISO 105-B02	>5
Colour fastness to rubbing wet	EN ISO 105-X12	>3
Colour fastness to rubbing dry	EN ISO 105-X12	>3-4
Colourfast. to water patterned	EN ISO 105-E01	>4

Safety & Environment

CE Labeling	EN 14041	Certified
Fire classifications	EN 14041	Efl
Indoor air	DIM Certifikat RUSSIA	No.005 Approved

Guides

Installation+adhensive guide	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
Cleaning, stain removal	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais

Manufacturer

Factory certification	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	EMAS	Audited and verified by BVC
	OHSAS	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK

eTL = inhouse result from ege Test laboratory (ISO9001 certified)
 Due to continuing development in tests and products specifications and results may be changed without notice.