

soft dreams

Product Description

Construction

Product Description	Methods	Product Data
Structure	ISO 2424	Tufted cut pile
Gauge	ISO 2424	5/32
Pile material	DIR 96/73, 96/74	100% Polyamide
Coloration	-	Continue
Backing	eTL	CF - Comfort felt
Dimensions	CEN/TS 14159	400 cm
Total thickness	ISO 1765	12,7 mm.
Surface pile thickness	ISO 1766	9,7 mm.
Tufts	ISO 1763	48.700 pr. m2
Total carpet weight	ISO 8543	3.400 g/m2
Pile yarn weight	eTL	1.650 g/m2
Surface pile density	ISO 8543	0,137 g/cm3
Antisoiling protection	eTL	Yes

Performance ratings

Performance areas	EN 1307	32 Commercial - General
	eTL	
Luxury rating class	EN 1307	5
Static control	eTL	Permanently antistatic
Body walking test	ISO 6356	Antistatic
Suitable for heated floors	ISO 8302	Yes
Colour fastness to light	ISO 105-B02	>5
Colour fastness to rubbing wet	EN ISO 105-X12	>3
Colour fastness to rubbing dry	EN ISO 105-X12	>3-4
Colourfast. to water patterned	EN ISO 105-E01	>4

Safety & Environment

CE Labeling	EN 14041	Certified
Fire classifications	EN 14041	Efl
Indoor air	DIM Certifikat	No.006
	RUSSIA	Approved

Guides

Installation+adhensive guide	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
Cleaning, stain removal	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais

Manufacturer

Factory certification	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	EMAS	Audited and verified by BVC
	OHSAS	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK

eTL = inhouse result from ege Test laboratory (ISO9001 certified)
 Due to continuing development in tests and products specifications and
 results may be changed without notice.